



**JL AUDIO**  
*Ahead of the Curve™*

## 10TW3-D4

**Dual Voice Coil  
Subwoofer 25 cm**

**Power Handling**  
**400 Watts RMS / 800 Watts Max.**

### Technical Specifications

Impedance	Zn	2 x 4 Ohms
Voice Coil Diameter	Ø	41,3 mm
Max. Linear Excursion	Xmax	+/- 15,2 mm
Cone Area	Sd	365 cm <sup>2</sup>
Moving Mass	Mms	227,66 g
DC Resistance	Re	2 x 4,5 Ohms
Resonance Frequency	Fs	32,3 Hz
Mechanical Q-Factor	Qms	11,35
Electrical Q-Factor	Qes	0,656
Total Q-Factor	Qts	0,62
Equivalent Air Volume	VAS	19,82 L
Flux Density	B/L	25,23 N/A
Efficiency 1W/1m	SPL	82,1 dB

### Recommended Enclosure

Sealed Box	
Sealed Volume:	14,2 L
-3 dB Rolloff (F3):	40,09 Hz

### Mechanical Components

- Diecast Aluminium Basket
- Single Spider
- Injected PP Cone
- Dual Magnet
- Rubber Surround
- Magnet Size: Ø130 x 36 mm
- Aluminium Dustcap

### Dimensions & Weight

External Diameter:	267 mm
Mounting Diameter:	244 mm
Mounting Depth:	83 mm
Shipping Weight:	5,4 kg

