



JL AUDIO
Ahead of the Curve™

10W0V3-4

**Single Voice Coil
Subwoofer 25 cm**

Power Handling
300 Watts RMS / 600 Watts Max.

Recommended Enclosure

Sealed Box
Sealed Volume: 18,4 L
-3 dB Rolloff (F3): 42,4 Hz

Technical Specifications

Impedance	Zn	4 Ohms
Voice Coil Diameter	Ø	50 mm
Max. Linear Excursion	Xmax	+/- 11,4 mm
Cone Area	Sd	316 cm ²
DC Resistance	Re	4,28 Ohms
Resonance Frequency	Fs	32,1 Hz
Mechanical Q-Factor	Qms	10,75
Electrical Q-Factor	Qes	0,64
Total Q-Factor	Qts	0,61
Equivalent Air Volume	VAS	31,1 L
Efficiency 1W/1m	SPL	84,1 dB

Recommended Enclosure

Ported Box
Vented Volume: 31,9 L
Port Diameter: 104 mm
Port Area: 85 cm²
Port Length: 81 cm
Tuning Freq. (Fb): 30 Hz
-3 dB Rolloff (F3): 29,6 Hz

Mechanical Components

- Steel Basket
- Polypropylen Cone
- Rubber Surround
- Single Spider
- Single Magnet
- Magnet Size: Ø128 mm

Dimensions & Weight

External Diameter: 267 mm
Mounting Diameter: 230 mm
Mounting Depth: 124 mm
Shipping Weight: 4,5 kg

