



JL AUDIO
Ahead of the Curve™

10W6V3-D4

**Dual Voice Coil
Subwoofer 25 cm**

Power Handling
600 Watts RMS / 1200 Watts Max.

Technical Specifications

Impedance	Zn	2 x 4 Ohms
Voice Coil Diameter	Ø	70 mm
Max. Linear Excursion	Xmax	+/- 19 mm
Cone Area	Sd	318 cm ²
DC Resistance	Re	2 x 3,23 Ohms
Resonance Frequency	Fs	30,12 Hz
Mechanical Q-Factor	Qms	9,228
Electrical Q-Factor	Qes	0,543
Total Q-Factor	Qts	0,513
Equivalent Air Volume	VAS	23,25 L
Efficiency 1W/1m	SPL	82,7 dB

Recommended Enclosure

Sealed Box	
Sealed Volume:	15,6 L
-3 dB Rolloff (F3):	42,3 Hz

Recommended Enclosure

Ported Box	
Vented Volume:	21,2 L
Port Area:	96 cm ²
Port Length:	77 cm
Tuning Freq. (Fb):	39 Hz
-3 dB Rolloff (F3):	33 Hz

Mechanical Components

- Diecast Aluminium Basket
- Single Spider
- Injected PP Cone
- Dual Magnet
- Rubber Surround
- Magnet Size: Ø160 x 44 mm

Dimensions & Weight

External Diameter:	267 mm
Mounting Diameter:	229 mm
Mounting Depth:	175 mm
Shipping Weight:	11,2 kg

