



JL AUDIO
Ahead of the Curve™

10W7-3

**Single Voice Coil
Subwoofer 25 cm**

Power Handling
750 Watts RMS / 1.500 Watts Max.

Recommended Enclosure

Sealed Box
Sealed Volume: 35,4 L
-3 dB Rolloff (F3): 40,7 Hz

Technical Specifications

Impedance	Zn	3 Ohms
Voice Coil Diameter	Ø	70 mm
Max. Linear Excursion	Xmax	+/- 23 mm
Cone Area	Sd	386 cm ²
DC Resistance	Re	2,75 Ohms
Resonance Frequency	Fs	30,6 Hz
Mechanical Q-Factor	Qms	7,65
Electrical Q-Factor	Qes	0,59
Total Q-Factor	Qts	0,54
Equivalent Air Volume	VAS	36,1 L
Efficiency 1W/1m	SPL	84,3 dB

Recommended Enclosure

Ported Box
Vented Volume: 42,5 L
Port Area: 116 cm²
Port Length: 57 cm
Tuning Freq. (Fb): 35,3 Hz
-3 dB Rolloff (F3): 32 Hz

Mechanical Components

- Diecast Aluminium Basket
- Single Spider
- Injected PP Cone
- Dual Magnet
- Rubber Surround

Dimensions & Weight

External Diameter: 267 mm
Mounting Diameter: 222 mm
Mounting Depth: 203 mm
Shipping Weight: 18,1 kg

